Garage door openers







Comfort 260, 270, 280

Comfort 260, 270 speed

Comfort 260 accu



Comfort 360, 370, 380

You want your own labeling on our garage door openers?
Almost all of the following products are also available on request as a neutral variant or with your very own labeling.

Technical data

	Comfort 260	Comfort 270	Comfort 280	Comfort 260 speed	Comfort 270 speed	Comfort 260 accu
Width overhead doors (max.) [m]	3.5	5	6	3.5	5	3.5
Width of tipping and canopy gates (max.) [m]	3.5	5	6	3.5	5	3.5
Height of tilt and canopy gates (max.) [m]	2.25					
Width of single-wall sectional doors (max.) [m]	5	5.5	6	5	5.5	5
Width of double-walled sectional doors (max.) [m]	3	5.5	6	3	5.5	3
Gate weight (max.) [kg]	90	165	200	110	185	90
Push and pull force (max.) [N]	550	750	1,000	650	850	550
Running speed (max.) [cm/s]	16			22	23.5	16
Cycles per hour (max.)*	2	4	6	3	4	2
Cycles per day (max.)	16	28	48	20	32	16
Operating voltage [V]	230 V/1~					24 V-DC
Nominal frequency [Hz]	50/60					
Rated current [A]	1.1					
Power consumption [VA/W/kW]	0.25 kW					0.12 kW
Power consumption in standby [VA/W/kW]	4 W					0.1 W
Motor voltage [V]	24 V-DC					
Control voltage [V]	24 V-DC					
Protection class	II					
Protection class	IP20					
Illuminant	8 LED module					
Continuous sound pressure level (max.) [dB(A)]	70					
Temperature (min./max.) [°C]	-20/60					
Dimensions (WxHxD) [mm]	190x125x360					
Weight [kg]	3.2	3.5	3.8		4.4	3.2

* One cycle corresponds to two travels (opening and closing) of the gate.